Office Copy has Thousand Island
Township of Lease Thousand Island

Felo Copy - as per By law 11-1981 with amederal Schools allached from By law 18-82.

> Please Return To Township of Leads and The Thougand Islands 1 Jessie St., Box 129 Lansdowne, ON KOE 1LO

ENGINEER'S REPORT

FOR THE CONSTRUCTION OF THE

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF REAR OF LEEDS & LANSDOWNE

A.J. GRAHAM ENGINEERING CONSULTANTS LTD. BOX 917, R.R. #3 OTTAWA, ONTARIO K1G 3N3

PROJECT 30089 MARCH 17, 1981

BY-LAW COPY



The Corporation of the Township of Rear of Leeds and Lansdowne

Clerk-Treasurer — Mrs. Alexia M. Landon, B.A., AMCT Deputy Clerk-Treasurer — Mrs. Carole Johnston Roads Superintendent — Laurence Hudson



P.O. Box 160, Lyndhurst, Ont. K0E 1N0
Offices on County Road No. 2
Telephone: Municipal (613) 928-2423
Roads --- (613) 928-2144

November 23, 1982

TO ALL PERSONS ASSESSED ON BIERMAN DRAIN:

The enclosed Tax Bill is for your Net Assessment of the costs of the Bierman Municipal Drain. Also enclosed is a copy of Annex C -Schedule of Assessments, revised by By-law 18-1982 to reflect the increased cost and increased grants.

The increase is due to:

(1) Construction costs - some sloughing in occurred as a result of unstable soils encountered during construction. Additional equipment rental and rip rap were required to overcome this. As well, tile outlets were found that required outlet pipes and rip rap.

(2) Engineering costs increased as a result of the above which required additional engineering and time. The completion of the work also took longer than originally anticipated.

(3) Further costs were incurred as interest charged by the Township on advances made from time to time from April of 1981 to October, 1982.

Alexia Landon.

THE CORPORATION OF THE TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

BY-LAW 18-1982

A BY-LAW TO AMEND BY-LAW 11-1981 BEING A BY-LAW TO PROVIDE FOR A DRAINAGE WORKS IN THE TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE IN THE COUNTY OF LEEDS AND TO RESCIND BY-LAW 17-1982

WHEREAS By-law 11-1981 authorized construction of a drainage works, known as the Bierman Drain,

AND WHEREAS the final cost of this drainage works is \$66245.30,

AND WHEREAS assessments in the Engineer's Report must therefore be increased,

NOW THEREFORE the council of the Township of Rear of Leeds and Lansdowne enacts as follows:

- All assessments set out in Annex C-Schedule of Assessment to Engineer's Report for the construction of the Bierman Municipal Drain shall be increased by a factor of 1.31267 because of the increase in cost over estimate, and the Grant factor shall be .6279462 to reflect the Federal and Provincial grants on the actual cost of the works.
- All assessments shall be due and payable December 15, 1982, and if not paid by such date shall be charged an interest rate thereon as provided for unpaid taxes, as set by by-law from time to time.
- 3. By-law 17-1982 be and the same is hereby rescinded.
- 4. This by-law comes into force on the passing thereof.

READ A FIRST, SECOND AND THIRD TIME THIS 22ND DAY OF NOVEMBER, 1982, AND GIVEN UNDER THE SEAL OF THE CORPORATION OF THE TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE THIS 22ND DAY OF NOVEMBER, 1982.

Ray Greenhern Went TREASURER

+13 12 +16 13 9 13 KRMAN 12 12 رر OF KEAR OF LEEDS AND LANSDOWNE 0 J. + M. Doubs J. + M. Doubs TOWNSHIP ROAD J. FRYE TOWNSHIP ROAD J.+ M. MOORE HIGHWAY #42 W. + M. CURTIS F. + E. GRAY TOWNSHIP G. FISCHER H. 4. G. REED M. RENE TOTALS 3340G FRYC + N. WALLS BICRMAN BICRMAN Nokes HOWARD ROAD ORAIN * * * * * 5 33 00 00 08 2 6624530 413-19 6303 24 53 049 200 5782 5782 37.71 30 S 8 ASSESS MENTS 10149 106451 3426 2217 32.82 63,03 5538 00 3260 51 950.95 1825 6210.48 101.49 50922 878 27 655 84 5301 -8529 63.03 3.79 E3 36843 VOVEMBER 3, 1982

THE CORPORATION OF THE TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

BY-LAW 18-1982

A BY-LAW TO AMEND BY-LAW 11-1981 BEING A BY-LAW TO PROVIDE FOR A DRAINAGE WORKS IN THE TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE IN THE COUNTY OF LEEDS AND TO RESCIND BY-LAW 17-1982

WHEREAS By-law 11-1981 authorized construction of a drainage works, known as the Bierman Drain,

AND WHEREAS the final cost of this drainage works is \$66245.30,

AND WHEREAS assessments in the Engineer's Report must therefore be increased,

NOW THEREFORE the council of the Township of Rear of Leeds and Lansdowne enacts as follows:

- 1. All assessments set out in Annex C-Schedule of Assessment to Engineer's Report for the construction of the Bierman Municipal Drain shall be increased by a factor of 1.31267 because of the increase in cost over estimate, and the Grant factor shall be .6279462 to reflect the Federal and Provincial grants on the actual cost of the works.
- 2. All assessments shall be due and payable December 15, 1982, and if not paid by such date shall be charged an interest rate thereon as provided for unpaid taxes, as set by by-law from time to time.
- 3. By-law 17-1982 be and the same is hereby rescinded.
- 4. This by-law comes into force on the passing thereof.

READ A FIRST, SECOND AND THIRD TIME THIS 22ND DAY OF NOVEMBER, 1982, AND GIVEN UNDER THE SEAL OF THE CORPORATION OF THE TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE THIS 22ND DAY OF NOVEMBER, 1982.

REEVE Jeenhem

SECRETARY-TREASURER

ENGINEER'S REPORT

FOR THE CONSTRUCTION OF THE

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF THE REAR OF LEEDS AND LANSDOWNE

A.J. Graham Engineering Consultants Ltd. Box 917, R.R. 5 Ottawa, Ontario K1G 3N3 Project 30089

March 17, 1981 Revised May 6, 1981 The Reeve and Members of Council Rear of Leeds and Lansdowne Seeley's Bay, Ontario KOH 2NO

REPORT FOR THE CONSTRUCTION OF THE BIERMAN MUNICIPAL DRAIN

I am pleased to present for Council's consideration the following Drainage Report for the construction of the Bierman Municipal Drain.

This Report has been prepared under the authority of Section 4, The Drainage Act, 1975, as amended.

SYNOPSIS OF REPORT

The body of the Report deals with the various aspects of municipal drainage including such items as Location, Inspection, Allowances, Grant Structure, Future Maintenance, etc.

Once the By-Law has been passed the Municipality has no authority to alter the assessments or make any revisions which alter the intent of the Report under The Drainage Act, 1975, as amended.

It is therefore important that any desired changes relating to construction be requested at the Meeting to Consider the Report.

The property owners are requested to examine the entire Report as it relates to their own properties, with particular attention to the following items:

1. Location of the Properties

The description and ownership of the properties have been obtained from the last revised Municipal Assessment Rolls and may not be changed until the Assessment Rolls are next revised.

All assessed owners are asked to check the description and location of their property in this Report and point out any errors or omissions at the Meeting to Consider the Report.

1.

2. Location of the Drain

All assessed owners are also requested to refer to the plans to confirm that the drains are located as desired on the particular properties.

3. Agricultrual Land Designations (Annex "C")

Note that non-agricultural lands listed in Annex "C" are denoted with an asterisk. These lands are not eligible for subsidy under The Drainage Act, 1975, as amended. Please note that in accordance with provincial requirements, the areas in Annex "C" are expressed in hectares (1 ha = 2.47 acres).

4. Disposal of Materials

Refer to the Earth Disposal and Spoil Pile Disposal Schedules in the Special Provisions and ensure that the disposal locations, material spreading provisions, etc., are as desired on your particular property or properties.

5. Private Culverts

Refer to the Private Culverts section of the Special Provisions and ensure that you have been provided with the required number of culverts and that they are located as desired on your property or properties. Note that the lane width provided by new culverts is approximately $5\ \mathrm{m}$ (16 feet) unless specifically otherwise requested.

The "Annex" portion of the Report deals with the following:

Annex "A" - Estimated Construction, Allowance, and Administration Costs

Annex "B" - Schedule of Allowances (Land or Crop Damage, Land Allowance and Severance) to affected properties

Annex "C" - Schedule of Assessment (Estimated Individual Assessment)

Annex "D" - Summary of Assessment

Annex "E" - Plans and Profiles

AREA REQUIRING DRAINAGE

From an examination of the site we have determined that the "Area Requiring Drainage" is located within the following lands:

Part Lots 8 to 12 Concession 12 Part Lots 8 & 9 Concession 13

LOCATION OF THE DRAIN

The Bierman Municipal Drain commences in the centre of the $E^{1/2}$ of Lot 8, Concession 12, at a point approximately 200 metres north of the abandoned railway line.

From this point the drain flows in an easterly direction across the W_2 of Lot 9, then turns southeasterly through the abandoned railway line and runs parallel, following the existing course, for a distance of approximately 130 metres. At this point the drain turns north through the rail line, thence easterly through the E. Pt. of Lot 9, and the W. Pt. of Lot 10, Concession 12.

The drain then flows in a northeasterly direction across the N. Pt. of Lot 10, Lot 11, amd the northwestern corner of Lot 12, thence through the Township road and across the southwestern corner of Lot 9, Concession 13 to the eastern edge of Lot 8, thence northerly through Highway 42, thence northeasterly trrough the Lake Street Road to its outlet in Lot 8, Concession 13.

The Bierman Municipal Drain is approximately 3,500 metres in length.

INSPECTION

From an inspection of the area and discussions with the resident property owners the following observations were noted.

Watershed Description

The watershed basin of the Bierman Municipal Drain is elongated with a main stream flow in a northeasterly direction.

The overall length of the drain inspected is approximately 3,500 metres and it provides outlet for approximately 235 hectares.

Existing Ditch

Throughout the area inspected the existing ditch is relatively shallow and has an irregular profile grade.

Rock outcroppings were observed at the Township Road between Concessions 12 and 13 and in the area of Highway 42.

INSPECTION (CONT'D)

Existing Ditch (Cont'd)

Several tile outlets were located in lots 11 and 12 concession 12 and despite some recent private channel improvements all the outlets were deficient in free board.

Soils

Reference to the Ministry of Agriculture and Food Soil Survey Reports indicated that the drain is located in an area of North Gower Clay Loam and Tennyson Loam.

The North Gower series is gently sloping and is stonefree while the Tennyson series is strongly sloping, is moderately stoney and is underlain with bedrock. Both series are stable and are not susceptible to erosion.

In general the Tennyson Series is location along the perimeter of the drainage basin but appears to extend to the proposed area of construction at several locations in concession 13.

Both soil classes are well suited for agricultural purposes when good drainage is available.

RECOMMENDATIONS

It is my recommendation that the Bierman Municipal Drain be constructed in accordance with the accompanying plan and profile. I feel the recommendations contained in this Report will provide the owners with the degree of drainage necessary for a viable farming operation.

Design

The drain shall be constructed as an open type trapezoidal channel with design dimensions as specified on Drawing No. 30089-1.

The new channel will be provided with a capacity suitable for agricultural surface drainage and sufficient profile depth to provide an outlet for all existing tile outlets. The channel provided attains sufficient outlet upstream of the Highway No. 42 culvert. Downstream of this drain, no increase in flows is estimated to occur from construction of this drain.

Disposal of Materials

Excavated earth material shall be spread on the private lands in accordance with Schedule No. 1 annexed to this Report.

RECOMMENDATIONS (CONT'D)

Disposal of Materials (Cont'd)

Excavated rock and boulders shall be disposed of by the contractor at a site provided for by him or incorporated into the work on approval of the Engineer.

The existing spoil piles shall be removed by the contractor. The class of material contained in the spoil piles will dictate whether the material will be spread or hauled away.

Tile Outlets

The existing tile outlets affected by this construction shall be reinstated and protected with random rip-rap.

Fencing

All cross-fences shall be opened and replaced by the contractor using new materials.

An existing parallel rail fence in the east part of lot 8 concession 13 will be removed by the contractor and the salvageable materials shall be piled clear of the work.

An allowance has been provided to the owner of the aforementioned lot as compensation for the re-instatement of this rail fence by the owner following construction.

Private Culverts

Private culverts have been provided as replacement for the existing crossing sites in use within the construction area.

Erosion Control

The contractor will be required to construct only one bank of the existing channel and the completed slope shall be seeded with an approved grass and legume seed mixture during the progression of work as weather permits.

AGRICULTURAL LAND DESIGNATION

Assessments for agricultural and non-agricultural lands are detailed in Annex "C" in accordance with Section 37 of The Drainage Act, 1975, as amended. Non-agricultural lands are denoted by an asterisk in Annex "C".

ALLOWANCES

Land Allowance: Section 29(a), The Drainage Act, 1975, as amended

Allowances for Land, as detailed in Annex "B", hereto attached will, in my opinion, adequately compensate the property owners indicated for the lands required for the construction of this drainage works.

Land or Crop Damage: Section 29(b), The Drainage Act, 1975, as amended

Allowances for Land or Crop Damage as detailed in Annex "B", hereto will, in my opinion, adequately compensate the property owners indicated for Land or Crop Damage caused by the construction of this drainage project.

In order to facilitate the disposal of material the property owners are advised to remove all crops adjacent to the drains prior to the start of construction.

Allowance for Fence: Section 30 The Drainage Act, 1975 as amended

The allowance for the re-instatement of the existing rail fence as detailed in Annex "B" will in my opinion adequately compensate the owner indicated for the loss of the fence.

Allowance for Private Drains: Section 31 The Drainage Act, 1975 as amended

The allowance for Private Drains as detailed in Annex "B" will in my opinion adequately compensate the owner indicated for the value of drainage work constructed privately to this project.

BRIDGES AND CULVERTS

Private Culverts: Section 18, The Drainage Act, 1975, as amended

Private culverts shall be supplied and installed by the Contractor and paid for by the drain.

BRIDGES AND CULVERTS (CONT'D)

Private Culverts (Cont'd)

Details in respect of the location of the culvert sites and required sizes may be found in the culvert schedule annexed to this Report.

Road Authority Bridges and Culverts: Section 17, The Drainage Act, 1975, as amended

The various Road Authority structures have been inspected throughout the course of the Drainage Works and the following improvements are recommended to provide satisfactory drainage to the agricultural lands.

Recommendations for improvements to Road Authority structures are made only when such structures are deficient in elevation or capacity necessary for agricultural drainage.

Minimum structure sizes as required in this Report are based on agricultural design ciriteria and are not based on the design criteria necessary to ensure the Ministry of Transportation and Communications subsidies.

The structure sizes and cost estimates recommended in this section are based on structure replacements in accordance with the Ministry of Transportation and Communications design criteria.

Site No. 1 Main Drain Sta. 2+426.6 Highway No. 42

The existing structure through Highway No. 42 in the above noted location has adequate capacity to carry agricultural flows and no replacement is recommended.

Site No. 2 Township Road Sta. 2+475 Main Drain

The existing culvert through the Township road in the above noted location has sufficient capacity for agricultural drainage and therefore replacement will not be necessary.

BRIDGES AND CULVERTS (CONT'D)

Road Authority Bridges and Culverts (Cont'd)

Site No. 3 Township Road Sta. 1+278 Main Drain

The existing structure through the Township Road in the above noted location is deficient in size and elevation and requires replacement.

A replacement structure sized in accordance with agricultural design criteria will require an effective end area, at design grade of 1.13 $\rm M^2$.

Using M.T.C. design criteria the minimum effective end area of the replacement structure will be $2.01~\text{M}^2$ and the cost of this work will be approximately \$7,800.

ROAD CULVERT COSTS

In accordance with Section 26 of The Drainage Act, 1975 as amended, the increased cost of this work caused by the existence of the road is chargeable directly to the Road Authority in addition to all other sums charged against the Road Authority when the work is completed as part of the Drainage Report. The estimated costs of replacement above have therefore been included in Annex C as a Special Assessment against the road authority.

The Road Authority may exercise the option under Section 69 of The Drainage Act, 1975, as amended, to have this work completed by their Road Department or completed as part of this Report.

Should the Road Authority opt to complete the work with their own forces, then the Special Assessment shall be deleted from this Report prior to the preparation of the final assessments.

LATERALS

It should be noted that the proposed drainage system will not immediately improve all wet areas unless lateral drains are constructed by the property owners.

The construction and maintenance of all lateral drains is the responsibility of the individual property owner and is not eligible for subsidy under the present municipal grant structure.

GRANTS

Under Sections 87, 88, 89 and 90 of The Drainage Act, 1975, as amended a Provincial grant of one-third of the cost of the project assessable to agricultural lands may be obtained.

Under the recently signed Eastern Ontario Subsidiary Agreement, there may be Federal assistance available for this project. Based upon the general criteria guidelines in that Agreement, the amount of Federal grant is estimated at 33 1/3% of the total project costs estimated in this Report.

At the time of writing this Report, an application for Federal grant has not been processed. The Federal grant amounts in this Report are dependent upon approval of the application for grant by the Drainage Petition Review Committee.

The Schedule of Assessment, Annex "C", has been computed based upon an estimated Provincial grant of 33 1/3% and estimated Federal grant of 33 1/3% for a total grant amount of 66 2/3% in respect of assessments against agricultural lands.

DISTRIBUTION OF COSTS

The estimated costs for this construction are apportioned to the properties responsible for Benefit and Outlet as determined by their area, locations, and run-off.

The detailed estimated Schedule of Assessment is attached in Annex "C" hereto, together with the estimated abatements of grants and allowances and my estimate of the net cost to each land owner in the project.

The estimated project cost (Annex "A") and assessment and grant amounts (Annex "C") are estimates only. The final assessments will be determined upon completion of the project based upon the actual project costs and actual grants secured with individual final assessment amounts determined pro-rata with the assessments in this Report and as may be revised by the Court of Revision.

WATER GATES

Fence lines crossing the drain tend to collect debris and often cause a restriction in flow. Further, they are often damaged during Spring flooding.

WATER GATES (CONT'D)

I therefore suggest that the respective property owners install water gates as detailed in Standard Drawing No. 7920, attached, after the completion of construction.

Water gates must be removed each fall by the respective property owners.

FUTURE MAINTENANCE

Future Maintenance of this project shall be the responsibility of the Township of the Rear of Leeds and Lansdowne.

Future Maintenance costs shall be levied to the lands upstream from the point of maintenance pro-rata with the assessments contained in this Report.

The Contractor shall be responsible for making good any construction defects found in his work for a period of one year from the date of final acceptance of the work. This obligation shall include such items as repair of culverts but shall not include for normal erosion or sedimentation of the drain.

The repair and maintenance of all private culverts installed under this Report shall be the responsibility of the Rear of Leeds and Lansdowne. The cost of all repairs subsequent to the expiry of the Guaranteed Maintenance will be charged as a Maintenance item.

The repair and maintenance of all fences installed under this report shall be the responsibility of the respective land owners on whose lands they are installed. All fences so installed will not necessarily represent a true property line.

Special assessments are not to be considered when pro-rating maintenance costs.

Maintenance of a drainage works or part thereof is initiated by written notification from any owner affected by the condition of the drainage works on the clerk or head of the Municipality.

WORKING SPACE

For the purpose of this construction and for Future Maintenance purposes the Working Space shall be 300 feet (91 m) on each side of the drain.

PLANS, PROFILES AND SPECIFICATIONS

The Plans, Profiles and Specifications form a part of this Report and are attached in Annex "E". The construction of this drainage project shall be in accordance with the MTC General Conditions Form M-100, Form GEC 200, Form GEC 300, and Special Provisions Form GEC 500 and Standard Drawings Form GEC 600.

Respectfully submitted this 17th day of March, 1981, and revised May 6, 1981.

S. Company

Brian L. Boyd, P. Eng.

ANNEX "A"

ESTIMATED COSTS

BIERMAN MUNICIPAL DRAIN

REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

Construction

Clearing Earth Excavation and Spreading Rock Excavation and Disposal Spoil Pile Disposal Reinstate Tile Outlets New Fence Remove Existing Fence Private Culverts Removal of Culverts Random Rip-rap Slope Seeding Tender Call Construction Contingencies Construction Administration Township Road Culvert	Lump Sum 7,448 m ³ 142 m ³ Lump Sum 4 127 m 66 m 6 28 m 78 m 20,841 m ²	\$ 3,440.00 9,367.92 5,680.00 2,341.00 200.00 508.00 132.00 6,465.00 28.00 2,340.00 3,126.15 200.00 1,600.00 7,800.00	2500.00
		\$45,728.07	\$45,728.07
Allowance for Private Drain Allowance for Land Allowance for Land and Crop Damage		450.00 2,040.00 3,048.00	
		. 5 520 00	. 5 500 00
•		\$ 5,538.00	\$ 5,538.00
Administration			
Engineer's Fee (Survey, Plan and F On Site Meeting Meeting to Consider Court of Revision Printing of Reports	Report)	6,000.00 200.00 200.00 200.00 400.00	
		\$ 7,000.00	\$ 7,000.00



TOTAL REPORT ESTIMATE

\$58,266.07

A 3 GRAHAM ENGINEERING CONSULTANTS LTD FILE 30089 REAR LEEDS LANSDOWNE THILLATING MINTY

MUNICIPALITY- REAR LEEDS LANSHONNEDATE- 81-02-17

00 9133	00 8001	00 0006	00'0	00 051	6	IAIDI STASSASA		
00.8727	3048.00	00.0405	00.0	00 057	BEAR LEEDS LANSDOWNE	MUNICIPALITY INTAL=		
02,79	05.7E	00.09	•	4	MIAM	107°14 £1 4	G FISCHER	81
372.00	05.75	75.00			NIVH		,	2
	145.50	150.00			NIAM	8 13 E.PT.	A.HOWARD	41
05° 72L	415.50	315.00			NIAH	"ld"M % 1 8	M4+W CHRTIS	
1005001	00.276	450.00			HIAM	*1d £1 6	J.FRYE	
00.408	00 075	564.00			NIAM	12 12 N.PT.	E + N MALLS	
1524 20	05.57A	315.00		00°05t	MIAM	11 12 PT N 1/2	J.BTERMAN	
280.00	00"751	156.00		The state of the s	NIYW	10 12 N.PT.	H+C BEED	
05° £07	05.74S	00 951			NIAM	10 % A 01	M RENE	
05°252	05 051	105.00			MIAM	9 12 E pl.	E+F LAMING	S
00 ° 98	U0 ° 95	30.00			NIAM	8 15 E1/5 MI/S	E DUDGE	
U5°56	US 65	00 92			NITH	9 12 MI/2MI/2	SAUNG M+t	٤
00°E6	00°£9	30.00			NIVW	8 12 E 1/2	enuna M÷t	
JATOT	СВОЬ	ראַמט	SEVERANCE	SPECTAL	нзияян	LT CON DESCR	UMMED	ON

00.8655

YMMEX BESCHEDOTE DE PELOMANCES

TNITTATING MUNTY . REAR LEEDS LANSOOWNE PROJECT-RIERMAN FILE 30089 A J GRAHAM ENGINEERING CONSULTANTS LTD

MUNICIPALITY- REAR LEEDS LANSDOWNEDATE- 81-02-17

PG 1

ANNEY C-SCHEDULE OF ASSESSMENT CN LT DESCR NWNER HA #BRANCH BENEFTT DUTLET BASIC GRANT ALLOW NET 12 A W 1/2 I R VONMINDEN 229.83 MAIN 0.00 0.00 4.40 0.00 229.83 153.22 0.00 76.61 12 8 F 1/2 ROHOG M+1. C 1500.03 390,19 93.00 7.59 1500.03 390.19 1890.22 1260.15 93.00 537.07 12 0 W1/2W1/2 3 J+M DUUDS MAIN 298,63 937.52 95.50 937.52 6.09 298.63 1236.15 824.10 95.50 316.55 12 9 E1/2 W1/2 4 E DONGE MAIN 371,46 1147.51 86.00 7.59 1147.51 371.46 1518.97 1012.65 86.00 420.32 12 9 F PT. 5 F+L LAMING MAIN 476,47 1406.27 252.50 MAIN 0.00 308,11 0.00 17.58 1406.27 784.58 2190.85 1460.57 252.50 477.78 12 10 4.PT. A M RENE MAIN 1250,02 698.08 403.50 MAIN 401.88 0.00 0.00 25,00 1250.02 1099.96 2349.98 1566.65 403.50 379.83 12 10 N.PT. 7 H+G PEFD 905,43 MAIN 1615,02 280.00 25.50 905.43 2520.45 1680.30 1615.02 280.00 560.15 12 10 F.PT. 37 36 R J + M MODRE MAIN 0.00 0.00 1.00 0.00 37.36 37.36 24.91 0.00 12.45 12 11 PT N 1/2 9 J. RIERMAN MAIN 13798.97 1445,14 1234.50 52.00 1445.14 15244.11 10162.74 1234.50 3846.87 13798.97 12 11 PT N 1/2 10 8 NUKES * MAIN 0.00 25,00 0.00 .50± 0.00 25.00 25.00 0.00 0.00 25.00 . 12 12 8.PT.N 1/2 11 J.BIERMAN MAIN 207,80 0.00 0.00 8.00 207.80 0.00 207.80 138.53 0.00 69.27 12 12 N. PT. 12 E + N WALLS MAIN 550.49 7771.88 804.00 24.00 7771.88 8322.37 5548.25 550.49 804.00 1970.12

3,0

AGGREGATE TOTALS

NON-AG HA (*)

1 2 2 1 259,65

51.T

ES. 24411 00.8522 #8.54455 F0.88402 19.7707 61.80454

11485.23	00*8228	33442.84	L0 * 9970S	16.1207	43408.16	FANGDOKNE		BEVB		YTIJAGIDIMUM 4 GBA				
52*00	00.0	00.0	25,00	52,00	00.0		MYIN	* *00,5	×	. da qihenwot	22	8-,14	۲	13
60.80	00.0	00*0	20.84	40,69 50,84	00°0 00°0		MIAH			M.T.C. HWY 43	15	0111 01	¥	٤١
00°52	00.0	00°0	52°00	52,00 52,00	00.0		MIAM	*S.L.*		09 9WT	20	¥1,1a	15	S!
97.871	00.0	00.0	67.871	67,00 67,00	00,88 00,88	5	MIAM	*00°5	(ANS GIHRNWOT	61	P1,9 CN.13	टा	15
71.68-	05°46	49.91	00.55	00°52	00.0	å	NIVW	00%.		G FISCHER	¥I	Tnd.Ta	۷	13
FE.575	109.50 109.50 00.00 00.512	19.885!	1933.00	86°85 52°5 57°55	50.0101 00.00 0.00 50.0721		MIAM MIAM MIAM	01,"#1		G9Awo∺A	41	ʻ.Taʻ.a	¥	£i
£7°69£	754.50	28.7815	87.1852	09,20 p2,66	2185°24		HIAM	13,00		w.+w. Cupits	9 1	,Ta.w	¥	13
45.2501	1095.00 00.0 1095.00	45*0009	58.0906	210,46 14,015 74,455	82.858 00.0 82.8588		MIAH	00,91		1°EBAE	5 T	,*1 _d	6	13
£1.21	00.0	30.26	62°57	62,50 62,50	00.0		NIVH	00.5		-3.FRYE	77	.Ta.2	υľ	εı
82.25	00.0	11.84	51.07	51.07	00.0		NIAM	00,*5		4 T V D * T 4 * 4	. 7	*1a*N	. 7	5 (
NET	אררטא אררטא	TNARD	BASIC	137110	BENEFIT		RRANCH	* YH		E*+E'CBEA UMNEB	21	DE4CE		

ANNER C-SCHEDNIE OF ASSESSMENT

MUNICIPALITY- REAR LEEDS LANSDOWNEDATE- 81-02-17

A' 1 RRAHAM ENGINEERING CONSULTANTS LTD PROJECT-RIERMAN . FILE 30089

INITIATING MINTY PEAR LEEDS LANSDOWNE

5 94

ANNEX "D"

SUMMARY OF ASSESSMENT

BIERMAN MUNICIPAL DRAIN

REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

Physical Description

Total Area Assessed

235 Hectares

Total Length of Drain (Open) 3,500 Metres

Estimated Cost of the Work

Road Culvert (Special Construction Item)	\$ 7,800.00
Construction	31,463.07
Private Culverts	6,465.00
Allowances	5,538.00
Engineer's Report	6,000.00
Other Costs	1,000.00
eng.	

\$58,266.07

ANALYSIS OF ASSESSMENT

Municipal Ontario	(Special Assessment - Township	Culvert)	7,800.00 48.02
Municipal			228.79
Privately	Owned - Agricultural		50,164.26
Privately	Owned - Non-Agricultural		.25.00

58,266.07

Special Assessment Estimated Provincial Grant	7,800.00 1 6,715,4 2	16,721.42 A
Estimated E.O.S.A. Grant	1 6,715.4 2	16, 121.42
Allowances	5,538.00	,
Estimated Net Cost	1-1,497.23	11,485.23 4

ESTIMATED TOTAL COST

\$ 58,266.07

FORM GEC 500

SPECIAL PROVISIONS

FOR THE CONSTRUCTION OF

THE BIERMAN MUNICIPAL DRAIN

REAR OF LEEDS AND LANSDOWNE

A.J. Graham Engineering Consultants Ltd. Box 917, R.R. 5 Ottawa, Ontario KlG 3N3

Project 30089

A.J. GRAHAM ENGINEERING CONSULTANTS LTD.

SPECIAL PROVISIONS

INDEX

Section	
500	General
501	Working Area
502	Trial Section
503	Clearing
504	Excavation
505	Spoil Pile Disposal
506	Reinstate Tile Outlets
507	Fencing
508	Private Culverts
509	Removal of Culverts
510	Random Rip-Rap
511	Slope Seeding
512	Iltilities

A.J. GRAHAM ENGINEERING CONSULTANTS LTD.

SPECIAL PROVISIONS

500 GENERAL

These Special Provisions shall be read in conjunction with all other sections of the contract documents including:

General Conditions of Contract - MTC Form M-100

General Conditions Supplementary - Form GEC 200, dated April 1980

Specifications for Open Drains - Form GEC 300, dated April 1980

501 WORKING AREA

The working area shall be designated as 300 feet (91 m) from each side of the drain.

502 TRIAL SECTION

.

The Engineer may require the Contractor to complete an initial trial section of drain of adequate length to demonstrate the acceptability of the Contractor's proposed method of construction.

If the Contractor's method has not produced a drain conforming to the contract drawings and specifications, the Contractor shall, at his own expense, perform such remedial measures as are necessary to satisfy the contract requirements and shall change his method of construction and produce a further trial section. This process shall be repeated until the Contractor has demonstrated that his method of construction will produce a drain conforming to the contract requirements.

503 CLEARING

This work shall be completed in accordance with Form GEC 300, Section 301.

503.01 CLEARING SPECIAL

The contrator shall be required to close cut all trees and brush from within the cross-section of the drain between stations 2+410 to 2+500.

504 EXCAVATION

This work shall be completed in accordance with Form GEC 300, Section 303.

504.01 Earth Disposal Locations

The Contractor shall be required to spread earth material in the locations and to the depths specified in Schedule No. 1 annexed to these special provisions.

504.02 Rock Excavation

Rock excavated from the drain shall be disposed of by the Contractor at a site provided for by him.

Upon approval of the Engineer rock blasted from the drain meeting the material specifications for random rip-rap may be incorporated into the works for this purpose.

504.03 Excavations in Road Right-of-ways

There shall be no excavated materials disposed of within the Township or Highway right-of-ways.

505 SPOIL PILE DISPOSAL

This work shall be completed in accordance with Form GEC 300, Section 304.

505.01 Spoil Pile Locations

All existing spoil piles in the construction area.

506 REINSTATE TILE OUTLETS

This work shall be completed in accordance with Form GEC 300 Section 306.

506.01 Tile Outlet Schedule

	Sta.	Size of Pipe	Location
	0+678	2-150 mm	North Bank
	0+678	1-150 mm	South Bank
	0+955	1-150 mm	South Bank
*	0+955	1-150 mm	North Bank
	0+968	1-150 mm	South Bank

^{*} Denotes Outlet Not To Be Disturbed By Contractor

507 FENCING

This work shall be completed in accordance with Form GEC 300. Section 308.

507.01 Fencing Schedule

Schedule No. 2 annexed to these Special Provisions.

507.02 Removal of Existing Fence

An existing rail fence as noted in Schedule No. 3 annexed to these Special Provisions shall be taken down by the Contractor and all salvaged materials shall be piled neatly clear of the construction area.

507.03 Basis of Payment for 507.02

Payment shall be made to the Contractor at the tender unit price bid and shall include for all labour and equipment required to complete the work.

508 PRIVATE CULVERTS

This work shall be completed in accordance with Form GEC 300 Section 309.

508.01 Private Culvert Schedule

Schedule No. 4 annexed to these Special Provisions.

509 REMOVAL OF CULVERTS

This work shall be completed in accordance with Form GEC 300 Section 310.

Refer to Schedule No. 4 for existing structure details.

510 RANDOM RIP-RAP

This work shall be completed in accordance with GEC Form 300 Section 311.

510.01 Random Rip-Rap Schedule

Refer to Schedule No. 5 annexed to these Special Provisions.

511 SLOPE SEEDING

This work shall be completed in accordance with Form GEC 300 Section 314 in the areas designated by the Engineer.

512 UTILITIES

The Contractor is advised there are buried and aerial in the construction area. Refer to Form GEC 200, Section 208.

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

SPREADING LOCATION

Page 1 of 2

Station	Owner	Location	Spreading
	Owner	Location	Spreading
01008.0			
01000 0			
to 0+430.5	H.& G. Reed	South Side	@ 300 mm Depth
0+430.5 to 0+686	J. Bierman	North Side	@ 150 mm Depth
0+686 to 0+955.7	J. Bierman	North Side	@ 150 mm Dape.
0+955.7 to 1+057.9	E. & N. Walls	East Side	@ 150 mm Depth
1+057.9 to 1+270	E. & N. Walls	North Side	@ 150 mm Depth
1+270 to 1+284	Township Road	Dispose Mater	ial
1+284 to 1+787.5	J. Frye	South Side	@ 150 mm Depth
1+787.5 to 1+980	W. & M. Curtis	North Side	@ 150 mm Depth
1+980 to 2+158	W. & M. Curtis	North Side	@ 300 mm Depth
2+158 to 2+354	A. Howard	Either Side	@ 300 am Depth
2+354 to 2+410	A. Howard	South Side	@ 300 mm Depth
	0+430.5 to 0+686 0+686 to 0+955.7 0+955.7 to 1+057.9 1+057.9 to 1+270 1+270 to 1+284 1+284 to 1+787.5 to 1+980 1+980 to 2+158 2+158 to 2+354	0+430.5 0+430.5 to 0+686 0+686 0+955.7 0+955.7 to 1+057.9 1+057.9 to 1+270 1+270 to 1+284 1+284 to 1+787.5 1+787.5 to 1+980 1+980 to 2+158 2+158 to 2+354 A. Howard	to 0+430.5 0+430.5 to 0+686 J. Bierman North Side 0+686 0+686 J. Bierman North Side to 0+955.7 0+955.7 to 1+057.9 1+057.9 1+057.9 1+270 1+270 1+270 1+284 1+284 1-1284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284 1-14284

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

SPREADING LOCATION

Page 2 of 2

Lot Description		Station		Owner	Locat	ion		Spre	ead	ing
W.Pt. Lot 10 Conc. 12		0+000 to 0-250	М.	Rene	South	Side	@	300 г	nın	dep L
E.Pt. Lot 9 Conc. 12		0-250 to 0-580	E.	& L. Laming	South	Side	@	300 г	nm	depth
E ¹ 2,W ¹ 2,Lot 9 Conc. 12		0-580 to 0-680	Ε.	Dodge	South	Side	@	300 r	mm	depth
W ₂ ,W ₂ ,Lot 9 Conc. 12		0-680 to 0-790	J.	& M. Douds	South	Side.	@	300 1	mm	depth
E^{1}_{2} , Lot 8 Conc. 12	3	0-790 to 0-890	J.	& M. Douds	South	Side	@	300	mm	depth

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

NEW FENCING

Lot Description	Station	Owner	Est. Quantity	Description Of Work
N.Pt. Lot 10 Conc. 12	0+372	H. & G. Reed	11 m	Cross Fence
N.Pt. Lot 10 Conc. 12	0+430.5	H. & G. Reed	11 m	Cross Fence
Pt. Lot 11 Conc. 12	0+955.7	J. Bierman	15 m	Cross Fence
-	1+269.8	Township Road	15 m	Cross Fence
Lot 9 Conc. 13	1+787.5	F. Frye	15 m	Cross Fence
W. Pt. Lot 8 Conc. 13	2+157.9	W. & M. Curtis	15 m	Cross Fence
W ¹ ₂ , W ¹ ₂ , Lot 9 Conc. 12	0-680	J. & M. Douds	15 m	Cross Fence
E_2^1, W_2^1 , Lot 9 Conc. 12	0-580	E. Dodge	15 m	Cross Fence
E.Pt. Lot 9 Conc. 12	0-250	E. & L. Laming	15 m	Cross Fence
		Total	127 m	

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

REMOVE EXISTING RAIL FENCE

Lot Description	Station	Owner	Est. Quantity	Description Of Work
E.Pt. Lot 8 Conc. 13	2+350 to 2+410	A. Howard	66 m	Parallel Fence (Rail Fence)
Re-instatement of	this fence shall	be the responsib	oility of the	owner.

SCHEDULE NO. 4

BIERMAN MUNICIPAL DRAIN

TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

PRIVATE CULVERTS

Conc.	Lot	Owner	Culvert Req'd.	Existing
		* .		
12	Pt.11	J. Bierman	1000 mm x 8 m x 2.0 mm	6.5 m
13	Pt. 9	J. Frye	1400 mm x 8 m x 2.8 mm	None
13	Pt.8	W. & M. Curtis	1400 mm x 8 m x 2.8 mm	4.7 m
12	E ¹ 2, W ¹ 2, Lot 9	E. Dodge	600 mm x 8 m x 1.6 mm	None
12	E.Pt. 9	E. & L. Laming	800 mm x 8 m x 1.6 mm	None
12	N.Pt.10	H. & G. Reed	900 mm x 8 m x 1.6 mm	Plank Crossing

BIERMAN MUNICIPAL DRAIN


TOWNSHIP OF REAR OF LEEDS AND LANSDOWNE

PROJECT 30089

RIP-RAP

Location	Type of Protection	Estimated Quantity
Sta. 0+678, Both Banks, (3 Outlets)	Tile Outlet Protection	6 M ³
Sta. 0+955, Both Banks, (2 Outlets)	Tile Outlet Protection	4 M ³
Sta. 0+960, East Bank,	Bank, Tile Outlet, Ditch Inlet Protection	12 M ³
Sta. 1+057, West Bank,	Bank and Ditch Inlet Protection	15 M ³
Sta. 1+270, East Bank,	Bank Protection	15 M ³
Sta. 2+390 to 2+412 East Bank	Bank and Culvert Protection	26 M ³
		78 M ³

G.E.C FORM 600 STANDARD DRAWINGS



NOTES

- 1. No excavation within 1 metre (3 feet) of existing fence line.
- Side slopes and channel dimensions as per profile drawing.
- 3. No spoil or spreading within 3 metres (10 feet) of top of bank.
- 4. Spoil thickness, width and spreading, location to be per Special Provisions.
- 5. Waterways, as per G.E.C. Specifications For Open Drains.
- Where one-sided construction is specified the existing grassed slope shall be preserved.

	OPEN CHANNEL SYSTEMS				
	EARTH CUT CHANNEL				
Di	ESIGN	M.F.	N.T.S.	79-02-15	7902
A	A.J. Graham Engineering Consultants Ltd				
	Ottawa, Ontario				

RANDOM RIP-RAP

O.6m
or
I'MIN.

O.6m
or
I'MIN.

O.6m
or
O.6m
o

RIP-RAP

Rip-Rap is to consist of quarried rock fragments of a size approved by the Engineer. All rip-rap must be properly keyed as per drawing.

NOTE: ROUND FIELD STONES NOT ACCEPTABLE UNLESS ENCLOSED AT THE EXPENSE OF THE CONTRACTOR IN GABIONS OR RENO MATRESSES.

HAND LAID

- Rip-Rap shall commence in a trench below the toe of the bank to a depth of 24" (0.61 metres).
- Minimum size of material to be placed shall be 1 cu. ft.
- Stones shall be placed by machine or by hand to the required length, thickness and depth conforming to the lines given by the Engineer.
- Rock subject to marked deterioration by water or weather will not be accepted.
- The largest stones shall be placed in bottom slopes.
- Stones shall be assorted in the walls so that each rear stone will be imbedded into the slope of the embankment.
- No shaping will be required but the Rip-Rap shall be placed closely and voids chinked with spalls.

RANDOM RIP-RAP


Random Rip-Rap shall be placed by dumping stones into position over the surface to be rip-rapped or placing them by other means. Care need not be taken in placing stones in any particular order.


NOTE:

MEASUREMENT FOR PAYMENT

When Rip-Rap is called by the cubic yard, measurement shall be made in place and converted to cubic yards based on theoretical dimensions.

OPEN- CHANNEL SYSTEMS					
	RIP-RAP (BANK PROTECTION)				
DESIGN	M.F.	SCALE N.T.S.	79-02-15	7903	
A.J. Graham Engineering Consultants Ltd.					
6	Ottawa, Ontario				





Note: Round Field Stones Not Acceptable for Rip-Rap.


Note:

Note: Rip-Rap to be on a Slope of 1/2:1 Unless Otherwise Specified


OPEN - CHANNEL SYSTEMS RIP-RAP AT CULVERT DESIGN DELAKH SCALE TALE 79-02-15 7904 A.J. Graham Engineering Consultants Ltd. Ottawa, Ontario

8.

TILE OUTLET




- 1. Outlet to be continuous rigid pipe, minimum length 4 m.
- 2/3 of its length to be buried, per Section B, or recessed per Section A, as specified in the Special Provisions.
- 3. Overhang length to discharge at the toe of the bank.
- Pipe should angle slightly downstream so as not to impede normal drain flow.
- 5. Outlet to be 500 mm minimum above ditch bottom or as specified.
- 6. Tile to be slipped 150 mm into pipe and sealed with mortar.
- 7. Rip-rap to be placed on ditch bottom or slope as required to prevent erosion.
- 8. Rodent gate to be installed at pipe end.
- 9. End of tile trench to be rip-rapped with stone to prevent erosion. Rip-rap to be 1 m wide from invert to ditch bottom.




(INSTALLATION TO BE MADE BY OWNERS).

One length of No. 9 wire run from the anchor posts across the top of the fence will provide a hook-up for the gate when conditions warrant raising it clear of the drain.



FENCING SPECIFICATIONS



NOTE : MAXIMUM DISTANCE BETWEEN BRACE PANELS IS 660'

FENCE FABRIC - No 9-3/4 STANDARD, STYLE No: 948 MEETING C.S.A. STD. G42

F	The state of the s					
1		FENC	ING ST	ANDAR	DS .	
	FENCING SPECIFICATIONS					
	DESIGN	M.F.	SCALE N.T.S.	CATE 79-02-15	7921	
	A.J. Graham Engineering Consultants Ltd Ottawa, Ontario					
					Ontario	